

Silver Bull GmbH Unterkreuth 7 – 39018 Terlan (I)

Tel. (0039)0471-25 71 85 / Fax (0039)0471-25 86 89

www.silverbull.it – info@silverbull.it

Frizz-d

genious and simple

silver[®]
bull

sense & simplification



VARIANTS

Water-cooled Diesel energy Lombardini LDW 702

BASE

Two-wheel-drive

differential lock on the rear axle

working height max 2,70m

automatic slope compensation system laterally

active pendulum lock on the front axle für more stability

electrically adjustable platform

pivorable railings

front wheel steering/60° steering lock

safety programs

OPTIONAL

Front-forklift + rear-forklift + conveyor belt for big boxes

Four-wheel-drive

automatic slope in direction of travel

air compressor

Drawber + street homologation

radio with CD and USB

toolbox

Tyre selant for four wheels

Tecnical data sheet

Base

length of the Lifting Platform without the forklift	2.150mm
length of the Lifting Platform with the forklift – closed	3.150mm
longitude of the base	1.300mm
overall height retracted	2.350mm
slope in lateraly direction	20%
slope in direction of travel	30%
inside turning radius	1.500mm
minimum of the gorund deariance	180mm
steering system	wheel steering
ship lift	gap
max. permitted weight	D = 1.580kg
max. driving speed	D = 8km/h
propulsion	hydraulic motors
Lifting Platform	
max. working height	2.700mm
retracted working height	1.050mm
Length	2.000mm
standard width	1.300-2.400mm
optional width	1.200-2.300mm