

Silver Bull GmbH - Unterkreuth 7 – 39018 Terlan (BZ)

Tel. 0471 – 25 71 85 / Fax 0471 – 25 86 89

www.silverbull.it - info@silverbull.it

d-rexx

silver[®]
bull
sense & simplification



variants
Water-cooled Diesel engine Lombardini 2 cyl
Water-cooled Diesel engine Lombardini 3 cyl
basic model
two-wheel drive
differential lock on the rear axle
working height 2,60m by a 2,5m platform
working height 2,70m by a 3m platform
automatic slope laterally - 15%
active pendulum lock on the front axle
Elekrische mobile Podeste Arbeitsbühne
pivotable railings
front wheel steering with 45° steering lock
control panel with automatic functions
safety programmms
optional
front- and rear forklift, conveyor belt for big boxes
four-wheel-drive
automatic slope in direction of travel - 20%
automatic steering system beyond ultrasonic sensors
air compressor with a tank and 4 connections
drawbar with street homologation
radio
toolbox
harvesting box
tyre sealant for four wheels

technical data sheet	
base	
length of the platform without the forklift	3.200 mm
length of the platform with the forklift - closed	4.300 mm
longitude of the base	1.300 mm
overall height retracted	2.300 mm
slope in the laterally direction	15%
slope in the direction of travell	20%
inside turning radius	3.000 mm
minimum of the ground deariance	200 mm
steering system	wheel steering
ship lift	gap
max. permitted weight	2.000 KG
max. driving speed	8 km/h
propulsion	hydraulic motors
lifting platform	
max. working height	2.700 mm
retracted working height	1.000 mm
length	3.000 mm
stand width	1.300 - 2.400 mm